

Scope

ARDROX 9PR50A is a water-white, clear, mobile liquid. It has a low sulphur, halogen and alkali metal content.

ARDROX 9PR50A is a solvent precleaner and penetrant remover used for the removal of both red and fluorescent penetrants. It can also be used as a dry cleaning solvent to remove oils and greases.

ARDROX 9PR50A is available in bulk, aerosol and tubs of impregnated wipes.

Chemicals required

ARDROX 9PR50A

Method of use

For precleaning operations, ARDROX 9PR50A is used by spray, immersion, brushing or applying via a cloth.

After suitable precleaning, penetrant application and the necessary penetrant contact time, the excess penetrant is removed with a clean, dry, lint-free cloth or tissue. The next stage is to use ARDROX 9PR50A to remove the final traces of excess penetrant from the surface. This is best done by applying ARDROX 9PR50A to a cloth or tissue and then wiping over the surface with the cloth. The application of ARDROX 9PR50A via a cloth should be continued until the cloth picks up virtually no penetrant.

After removal of the excess penetrant, a thin even coat of developer is applied to the components to inspect for any defects.

When used as a dry cleaning solvent, ARDROX 9PR50A may be applied by any of the conventional methods such as spraying, dipping, brushing and swabbing. Soak tanks should be constructed with a lid in order to minimise solvent losses by evaporation.

Effects on materials

ARDROX 9PR50A is safe to use on all common metals, including stainless and mild steels, magnesium, aluminium, copper and cadmium. ARDROX 9PR50A may have a softening or swelling effect on some rubbers and plastics. This should be checked before use, where such materials are likely to be encountered.

Technical information

Appearance:	Clear, water-white, mobile liquid.
Density at 15°C:	0.71 g/ml
Flash point:	41°C

These are typical values only and do not constitute a specification.

Store in a cool dry place suitable for flammable solvents.

Equipment materials

Equipment/tanks should be constructed of stainless steel.

Safety guidance

Before operating the process described it is important that this complete document, together with any relevant Safety Data sheets, be read and understood.

General information

Chemetall PLC supplies a wide range of chemical products and associated equipment for cleaning, sanitising, descaling, paint and carbon removal, metal protection and non-destructive testing. Sales Executives are available to advise on specific problems and applications.

Labour and environmental protection

All local and national regulations on the transport, storage, use and waste treatment of chemicals in concentrated or diluted form and as working solutions must be obeyed.

Further specific information on the products can be found in the EC Safety Data Sheets supplied. The user should also pay strict attention to information and hazard symbols shown on product labels.

Waste disposal

All waste waters must be treated in accordance with national legislation and local regulations prior to discharge to the sewer.

Ic Feb 2001